Docket No.: Q198-US1

QUALLION LEGAL

Page 3

10. (previously presented) The device of claim 9, wherein each non-terminal silicon is linked to at least one side chain that includes a poly(alkylene oxide) moiety.

- 11. (canceled)
- 12. (previously presented) The device of claim 1, wherein the at least one side chain includes an oxygen linked to a silicon on the backbone.
- 13. (previously presented) The device of claim 1, wherein the polysiloxane is represented

where R is alkyl or aryl; R<sub>1</sub> is alkyl or aryl;

at least one of the 
$$R_3$$
 is represented by:
$$(CH_2)q-O$$
and the other

$$-R_9 - \begin{bmatrix} CH_2 - CH - O \end{bmatrix} R_8$$

$$p$$

$$Or$$

$$(CH_2)q - O$$

R<sub>3</sub> is represented by:

R4 is a cross link that links the polysiloxane backbone to another polysiloxane backbone;

$$-R_9 - \left[CH_2 - CH - O\right]_{p}^{R_7}$$

R<sub>5</sub> is represented by:

R<sub>6</sub> is represented by:

Docket No.: Q198-US1

Page 4

 $R_7$  is hydrogen; alkyl or aryl;  $R_8$  is alkyl or aryl;  $R_9$  is oxygen or an organic spacer;  $R_{10}$  is an oxygen or an organic spacer; k is greater than or equal to 0; p is 3 to 20; q is 1 to 2; m is greater than or equal to 0 and n is 2 to 25.

- 14. (previously presented) The device of claim 13, wherein a ratio of n:m is in a range of 10:1 to 100:1.
- 15. (canceled)
- 16. (previously presented) The device of claim 13, wherein at least one R<sub>3</sub> is represented

$$-R_9 - \left[CH_2 - CH - O\right]R_6$$

by:

- 17. (previously presented) The device of claim 16, wherein R<sub>9</sub> is an organic spacer.
- 18. (canceled)
- 19. (previously presented) The device of claim 13, wherein at least one R<sub>3</sub> has a different structure from another R<sub>3</sub>.
- 20. (previously presented) The device of claim 13, wherein each  $R_3$  has a different structure from each  $R_5$  and from each  $R_6$ .
- 21. (previously presented) The device of claim 1, wherein the average molecular weight for the polysiloxane is less than or equal to 3000 g/mole.
- 22. (previously presented) The device of claim 1, wherein the electrolyte includes lithium ions, and wherein a [O]/[Li] ratio is 5 to 50, [O] being the molar concentration of the active oxygens in the electrolyte and [Li] being the molar concentration of the lithium ions in the electrolyte.

Docket No.: Q198-US1

Page 5

- 23. (previously presented) The device of claim 1, wherein the electrolyte is a liquid.
- 24. (previously presented) The device of claim 1, wherein the electrolyte is a solid.
- 25. (canceled)
- 26. (previously presented) The device of claim 1, wherein the polysiloxane is a member of an interpenetrating network.
- 27. (previously presented) The device of claim 1, wherein the electrolyte has a conductivity better than  $1.0 \times 10^{-4}$  S/cm at 25 °C.
- 28-54. (canceled)
- 55. (previously presented) An electrochemical device, comprising: an electrolyte including a polysiloxane represented by:

where R is alkyl or aryl; R1 is alkyl or aryl;

$$-R_9 - CH_2 - CH - O = R_8$$

$$p$$

$$(CH_2)q - O$$

R<sub>3</sub> is represented by:

R4 is a cross link that links the polysiloxane backbone to another polysiloxane backbone;

$$-R_9 - CH_2 - CH_0 - O$$

R<sub>5</sub> is represented by:

Docket No.: Q198-US1

Page 6

R<sub>6</sub> is represented by:

 $R_7$  is hydrogen; alkyl or aryl;  $R_8$  is alkyl or aryl;  $R_9$  is oxygen or an organic spacer;  $R_{10}$  is an oxygen or an organic spacer; k is greater than or equal to 0; p is 3 to 20; q is 1 to 2; m is greater than or equal to 0 and n is 2 to 25.

- 56. (previously presented) The device of claim 55, wherein a ratio of n:m is in a range of 10:1 to 100:1.
- 57. (previously presented) The device of claim 55, wherein at least one R<sub>3</sub> is represented

$$-R_9 - CH_2 - CH - O R_8$$

by:

- 58. (previously presented) The device of claim 57, wherein R<sub>9</sub> is an organic spacer.
- 59. (previously presented) The device of claim 55, wherein at least one R3 is represented by:

$$-R_{10}$$
 $O$ 
 $CH_2)q-O$ 

- 60. (previously presented) The device of claim 55, wherein at least one  $R_3$  has a different structure from another  $R_3$ .
- 61. (previously presented) The device of claim 55, wherein each  $R_3$  has a different structure from each  $R_5$  and from each  $R_6$ .
- 62. (new) The device of claim 1, wherein the portion of the silicons being linked to the side chain that includes the poly(alkylene oxide) moiety excludes the one or more terminal

**20** 010/013

Application No: 10/810,019 Docket No.: Q198-US1

Page 7

silicons that are linked to the at least one side chain that includes the carbonate moiety.